

S 115 HFG Super



Construction

Composed of flexible and see-through PVC reinforced with rigid PVC helix joint both in one part. Smooth inside.

Characteristic

DESIGN. Conceived to resist damages of abrasion, corrosion and weather resistant.

TRANSPARENCY. It allows visual check of material flowing.

STRENGTH. Achieved because of the internal spiral.

COMPOSITION. It can be easily cut in any length.

TEMPERATURE. From -10 to +60°C.

Certificates: Food grade and A Bisphenol and Phthalates free. According CE 10/2011 and 2016/1416 standards.(C Simulant).

Application

Flow of wine and alcohol until 20% and food products. Non Toxic.

Nominal Diameter	Inside Diameter	Outside Diameter	Working pressure	Bursting Rating	Weight	Standard Length
mm	mm	mm	kgf/cm ² 20°C	kgf/cm ² 22°C	gr/m	m
30	30.0	35.0	11	30	440	50
32	32.0	37.0	11	30	530	50
35	35.0	40.0	11	30	600	50
40	40.0	50.0	11	30	850	50
45	45.0	53.5	11	30	900	50
50	50.0	60.0	10	25	1150	50
60	60.0	72.0	9	25	1500	50
70	70.0	82.0	8	23	1700	50
75	75.5	86.5	8	23	1800	50
80	80.0	92.5	7	20	2000	50
90	90.5	103.0	7	20	2300	30
100	100.5	113.5	6	18	3000	30
110	110.0	124.0	5	15	3300	30
125	125.0	145.0	4	14	4000	30
150	154.0	174.0	4	14	6500	20
200	200.0	222.0	4	12	10000	10