

S 100 Super



Construction

Polyurethane hose composed of transparent flexible PVC, reinforced with a smooth interior black PVC spiral.

Characteristics

DESIGN. Specially designed to resist damages from abrasion, corrosion and weather resistant.

TRANSPARENCY. It allows to see the transported material.

STRENGTH. Achieved because of the internal spiral.

TEMPERATURE. -5 to +60°C.

ANTISTATIC. Antistatic due to the copper wire placed inside. (Available on request).

Application

Absorption and/or impulsion of dry materials.

Agricultural industry vacuum system of abrasive materials.

Nominal Diameter	Inside Diameter	Outside Diameter	Working pressure	Bursting Rating	Weight	Standard Length
mm	mm	mm	kgf/cm ² 20°C	kgf/cm ² 22°C	gr/m	m
30	30.0	35.0	11	30	440	50
32	32.0	37.0	11	30	530	50
35	35.0	40.0	11	30	600	50
40	40.0	50.0	11	30	850	50
45	45.0	53.5	11	30	900	50
50	50.0	60.0	10	25	1150	50
60	60.0	72.0	9	25	1500	50
70	70.0	82.0	8	23	1700	50
75	75.5	86.5	8	23	1800	50
80	80.0	92.5	7	20	2000	50
90	90.5	103.0	7	20	2300	30
100	100.5	113.5	6	18	3000	30
110	110.0	124.0	5	15	3300	30
125	125.0	145.0	4	14	4000	30
150	154.0	174.0	4	14	6500	20
200	200.0	222.0	4	12	10000	10