

# S 112



## Construction

Hose made of flexible PVC, reinforced with a rigid PVC spiral. Smooth interior.

## Characteristics

**DESIGN.** Easy to handle because of its lightness.

**TRANSPARENCY.** It allows to see the material transferred.

**STRENGTH.** Achieved because of its internal spiral and resists damages from abrasion, corrosion and weather resistant.

**TEMPERATURE.** From  $-20^{\circ}\text{C}$  to  $60^{\circ}\text{C}$ .

## Application

Absorption and impulsion of liquids for agricultural and industrial irrigation.

Certificates: Food grade and A Bisphenol and Phthalates free. According CE 10/2011 and 2016/1416 . (A Simulant).

Nominal Diameter	Inside Diameter	Outside Diameter	Working pressure	Bursting Rating	Weight	Standard Length
mm	mm	mm	kgf/cm <sup>2</sup> 22°C	kgf/cm <sup>2</sup> 22°C	gr/m	m
20	20.0	24.5	7.0	25	210	50
25	25.0	30.0	7.0	25	270	50
30	30.0	35.0	7.0	25	340	50
32	32.0	37.0	7.0	25	360	50
35	35.0	40.5	6.0	22	450	50
40	40.0	46.0	6.0	22	530	50
45	45.0	52.0	6.0	22	670	50
50	50.5	57.5	5.0	20	750	50
55	55.5	62.5	5.0	20	960	50
60	60.5	68.5	5.0	20	1060	50
65	65.5	73.3	5.0	20	1120	50
70	70.5	79.5	5.0	20	1280	50
75	75.5	84.0	5.0	20	1380	50
80	80.5	91.0	5.0	20	1600	50
90	90.5	100.5	4.0	16	1950	30
100	100.5	111.5	4.0	16	2300	30
110	110.0	123.5	3.0	9	2600	30
125	125.0	137.0	2.5	8	3130	30
150	151.0	167.0	2.0	7	4885	20
200	200.0	217.0	1.0	4	7510	10