

114 Tricapa



Construction

Hose composed of flexible PVC, Nitrile Rubber (NBR) a rigid PVC helix and an interior layer of Polyurethane to improve the abrasion resistance.

Characteristics

DESIGN. Specially develop to resist the abrasion, corrosion and weather damages.

LIGHTNESS. Easy to handle due to its weight.

COMPOSITION. It can be easily cut in any length.

FLEXIBILITY. Very flexible specially in low temperatures.

TEMPERATURE. From -40°C a 50°C .

Application

Aspiration and impulsion of granulated materials, drains, slurry and liquids with solid particles.

Nominal Diameter	Inside Diameter	Outside Diameter	Working pressure	Vacuum Rating	Weight	Minimum Curvature Radius	Standard Length
mm	mm	mm	kgf/cm ² 22°C	kgf/cm ² 22°C	gr/m	mm 22°C	m
30	30	40	3	0.9	600	40	50
35	35	45	3	0.9	750	45	50
40	40	52	3	0.9	960	50	50
45	45	57	3	0.9	1050	55	50
50	50.5	62	3	0.9	1150	60	50
60	60.5	72	3	0.9	1500	80	50
65	65.5	77	3	0.9	1600	130	50
70	70.5	82	3	0.9	1700	140	50
75	75.5	87	3	0.9	1800	150	50
80	80	91.0	2.5	0.9	2000	160	50
90	90.5	100.5	2.5	0.8	2400	180	30
100	100.5	111.5	2.5	0.8	2620	200	30
110	110.0	123.5	2	0.8	3000	240	30
125	125.5	137.0	2	0.8	4200	300	30
150	153	167.0	2	0.8	5150	350	20
200	202	217.0	2	0.8	8400	600	10