

S 118



Construction

Hose made of flexible PVC and NBR rubber reinforced with a rigid PVC spiral. Smooth interior. Do not contain lead derivatives.

Characteristics

DESIGN. Easy to handle because of its lightness.

TRANSPARENCY. It allows to see the material transferred.

STRENGTH. Achieved because of its internal spiral and resists damages from abrasion, corrosion and weather resistant.

TEMPERATURE. From -30°C to 60°C .

Application

Transfer of industrial oils and petroleum-based fuels.

Nominal Diameter	Inside Diameter	Outside Diameter	Working pressure	Bursting Rating	Weight	Standard Length
mm	mm	mm	kgf/cm ² 22°C	kgf/cm ² 22°C	gr/m	m
30	30.0	35.0	11.0	30	440	50
32	32.0	37.0	11.0	30	530	50
35	35.0	40.0	11.0	30	600	50
40	40.0	50.0	11.0	30	850	50
45	45.0	53.5	11.0	30	900	50
50	50.0	60.0	10.0	25	1150	50
60	60.0	72.0	9.0	25	1500	50
70	70.0	82.0	8.0	23	1700	50
75	75.0	86.5	8.0	23	1800	50
80	80.0	92.5	7.0	20	2000	50
90	90.5	103.0	7.0	20	2300	30
100	100.5	113.5	6.0	15	3000	30
110	110.0	124.0	5.0	15	3300	30
125	125.0	145.0	4.0	14	4000	30
150	151.0	174.0	4.0	14	6500	20
200	200.0	222.0	4.0	12	10000	10