

S 170



Construction

Hose made of flexible and clear PVC, reinforced with a rigid grey PVC spiral. Smooth interior. Opaque grey available on request).

Characteristics

DESIGN. Specially designed to resist damages from abrasion, corrosion and weather resistant.

TRANSPARENCY. It allows to see the material transferred.

STRENGTH. Achieved because of its internal spiral.

TEMPERATURE. From -30°C to 60°C .

Available on request with copper wire.

Application

Absorption and/or discharge of septic tank, sewer, slurry,...

Agricultural industry, irrigation systems, waste disposal vehicles,...

Nominal Diameter	Inside Diameter	Outside Diameter	Working Pressure	Vacuum Rating	Minimum Bend Radius	Weight	Standard Length
mm	mm	mm	kgf/cm ² 20°C	kgf/cm ² 22°C	mm 22°C	gr/m	m
30	30.0	38	3	0.9	40	450	50
35	35.0	43	3	0.9	45	600	50
40	40.0	50	3	0.9	50	750	50
45	45.0	55	3	0.9	55	800	50
50	50.5	60	3	0.9	60	850	50
60	60.5	71	3	0.9	80	1050	50
65	65.5	76	3	0.9	130	1100	50
70	70.5	81	3	0.9	140	1250	50
75	75.5	86	3	0.9	150	1350	50
80	80	91	2.5	0.9	160	1500	50
90	90.5	104	2.5	0.8	180	2000	30
100	100.5	113	2.5	0.8	200	2300	30
110	110.0	124	2	0.8	240	2600	30
125	125.5	142	2	0.8	300	3600	30
150	153	170	2	0.8	350	4500	20
200	202	221	2	0.8	600	6600	10