

S 375



Construction

Hose composed with EPDM rubber reinforced with textile fiber and polyethylene external spiral.
Standard color: yellow spiral.

Characteristics

LIGHTNESS. Easy to manipulate due to its lightweight.

DESIGN. The spiral gives more resistance to abrasion, corrosion and weathering and provides for easier drag.

FLEXIBILITY. Recovery of 90% of shape in case of flattening.

STRENGTH. The textile reinforcement allows more resistance higher pressure.

COMPOSITION. It can be cut easily in any length.

TEMPERATURE. From -20°C to $+60^{\circ}\text{C}$.

Application

Aspiration and impulsion of residual water, salt water, chemical products, mining, construction industry and septic tank.

Nominal Diameter	Inner Diameter	Outer Diameter	Work Pressure	Minimum Curvature Radius	Vacuum rating	Weight	Standard Length
mm	mm	mm	kgf/cm ² 22°C	kgf/cm ² 20°C	Kgf/cm ² 22°C	gr/m	m
32	30,5	42,5	8.0	80	0,9	650	40
35	34,2	43,8	8.0	80	0,9	750	40
40	38,2	48,6	8.0	80	0,9	898	40
45	44,2	54,6	8.0	80	0,9	1046	40
50	51,4	63,5	8.0	130	0,9	1226	40
55	54,3	66	8.0	130	0,9	1396	40
65	63,5	79	6.0	150	0,9	1650	20
70	69,3	83,4	6.0	150	0,9	1760	20
75	76,2	91,7	6.0	180	0,9	1900	20
90	89,3	103,5	5.0	300	0,9	2598	20
100	103	120	5.0	300	0,9	2913	20