

S 170 Tricapa



Construction

Hose made of flexible and clear PVC, reinforced with a rigid grey PVC spiral and polyurethane layer to increase the resistance to the abrasion. Smooth interior and corrugated exterior.

Characteristics

DESIGN. Specially designed to resist damages from abrasion, corrosion and weather resistant.

TRANSPARENCY. It allows to see the material transferred.

STRENGTH. Achieved because of its internal spiral.

TEMPERATURE. From -25°C to 60°C .

Available on request with copper wire.

Application

Absorption and/or discharge of cereals, grains, pellet, abrasive materials...

Agricultural industry, irrigation systems, waste disposal vehicles,...

Nominal Diameter	Inside Diameter	Outside Diameter	Working Pressure	Vacuum Rating	Minimum Bend Radius	Weight	Standard Length
mm	mm	mm	kgf/cm ² 20°C	kgf/cm ² 22°C	mm 22°C	gr/m	m
30	30	40	3	0.9	40	600	50
35	35	45	3	0.9	45	750	50
40	40	52	3	0.9	50	960	50
45	45	57	3	0.9	55	1050	50
50	50.5	62	3	0.9	60	1150	50
60	60.5	72	3	0.9	80	1500	50
65	65.5	77	3	0.9	130	1600	50
70	70.5	82	3	0.9	140	1700	50
75	75.5	87	3	0.9	150	1800	50
80	80	91.0	2.5	0.9	160	2000	50
90	90.5	100.5	2.5	0.8	180	2400	30
100	100.5	111.5	2.5	0.8	200	2620	30
110	110.0	123.5	2	0.8	240	3000	30
125	125.5	137.0	2	0.8	300	4200	30
150	153	167.0	2	0.8	350	5150	20
200	202	217.0	2	0.8	600	8400	10